PATENT COOPERATION TREATY

PCT

REC'D 10 FEB 2005 WIPO

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference			nt's file reference	FOR FURTHER AC	ACTION See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)			
International application No.			eation No	International filing date (a			Priority date (day/month/ye	
PCT/IT 03/00034				29.01.2003	y/////////	.,,	29.01.2003	•
Intern	ational	Pater	nt Classification (IPC) or bo	th national classification ar	nd IPC		<u> </u>	······································
	C3/06		, ,					
Appli	cant							
BEN	ICO F	ACK	S.p.A. et al.		•			
1.	This	intern	ational preliminary exar	nination report has beer applicant according to A	prepare	ed by this Inte	rnational Preliminary Exa	mining
	Aum	only a	ing is transmitted to the	applicant according to A	TI LICIE OF	J.		
					-14			
2.	This	REPO	ORT consists of a total of	of 4 sheets, including the	is cover	sneet.		,
	\boxtimes	This	report is also accompa	nied by ANNEXES, i.e. s	NEXES, i.e. sheets of the description, claims and/or drawings which have nis report and/or sheets containing rectifications made before this Authority			
		beer (see	n amended and are the l Rule 70.16 and Section	basis for this report and/ n 607 of the Administrati	or sheet ve Instru	is containing r actions under t	ectifications made before the PCT).	this Authority
	Thes		nexes consist of a total of					
	******	.	,0,00					
						<u>,</u>		
								•
3.	This	repoi	t contains indications re	lating to the following ite	ems:			
	1	☒	Basis of the opinion				•	
	II		Priority					
	III Non-establishment of opinion with regard to novelty, inventive step and industrial applicability							
1	IV		Lack of unity of invent		th roson	d to novolty ir	wantiwa etan ar industrial	applicability:
ļ	V	×	citations and explanat	ions supporting such sta	ui regan itement	u to noveity, ii	ventive step or industrial	applicability,
	VI		Certain documents cit	ed				
	VII		Certain defects in the	international application				
	VIII		Certain observations	on the international appl	ication			
Date of submission of the demand Date of completion of this report								
Date of submission of the demand			Date of	completion of t	nis report			
01.06,2004			09.02	.2005				
01.00.2004			00.02					
Name and mailing address of the international				Authori	zed Officer		Allertan Patron	
preliminary examining authority: European Patent Office]	_			
	<u>)</u>	D- Te	80298 Munich I. +49 89 2399 - 0 Tx: 5236	656 epmu d	Balz,	O		
Fax: +49 89 2399 - 4465			Teleph	one No. +49 89	2399-7218	Diges sand		

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/IT 03/00034

	Basis	_£ 4h	
•	Hasis	Of the	report

1. With regard to the **elements** of the international application (Replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report since they do not contain amendments (Rules 70.16 and 70.17)):

	Des	cription, Pages	
	1, 3-	8	as originally filed
	2, 2	a, 2b	filed with telefax on 25.01.2005
	Clai	ms, Numbers	
	1-10		filed with telefax on 25.01.2005
	Drav	wings, Sheets	
	1/9-9	9/9	as originally filed
2. With re langua		regard to the langua uage in which the inte	age, all the elements marked above were available or furnished to this Authority in the ernational application was filed, unless otherwise indicated under this item.
	The	se elements were ava	ailable or furnished to this Authority in the following language: , which is:
		the language of a trai	nslation furnished for the purposes of the international search (under Rule 23.1(b)).
		the language of publi	ication of the international application (under Rule 48.3(b)).
		the language of a train Rule 55.2 and/or 55.3	nslation furnished for the purposes of international preliminary examination (under 3).
3.	With inte	n regard to any nucle ornational preliminary e	otide and/or amino acid sequence disclosed in the international application, the examination was carried out on the basis of the sequence listing:
		contained in the inter	mational application in written form.
		filed together with the	e international application in computer readable form.
		furnished subsequen	ntly to this Authority in written form.
		furnished subsequen	ntly to this Authority in computer readable form.
		The statement that the in the international ap	he subsequently furnished written sequence listing does not go beyond the disclosure pplication as filed has been furnished.
		The statement that the listing has been furni	he information recorded in computer readable form is identical to the written sequence ished.
4.	The	amendments have re	esulted in the cancellation of:
		the description,	pages:
		the claims,	Nos.:
		the drawings,	sheets:

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/IT 03/00034

5. 🏻	This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed (Rule 70.2(c)).
	to the second to

(Any replacement sheet containing such amendments must be referred to under item 1 and annexed to this report.)

6. Additional observations, if necessary:

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N) Yes: Claims 1-10

No: Claims

Inventive step (IS) Yes: Claims 1-10

No: Claims

Industrial applicability (IA) Yes: Claims 1-10

No: Claims

2. Citations and explanations

see separate sheet

Re Item V

Reasoned statement with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

- 1. Reference is made to the following document/s/:
 - D1: DE 100 23 658 C (ADOLF ILLIG MASCHB GMBH & CO K) 18 October 2001 (2001-10-18)
 - D2: US-A-4 208 237 (HEYNE CLARENCE A) 17 June 1980 (1980-06-17)
 - D3: PATENT ABSTRACTS OF JAPAN vol. 010, no. 077 (M-464), 26 March 1986 (1986-03-26) & JP 60 219030 A (FUJI SEAL KOGYO KK), 1 November 1985 (1985-11-01)
 - D4: US-A-3 767 496 (DOHERTY T ET AL) 23 October 1973 (1973-10-23)
 - D5: DE 198 59 063 A (BERRENBAUM FRANK) 29 June 2000 (2000-06-29)
- 2. The document D1 is regarded as being the closest prior art to the subject-matter of claim 1, and shows (the references in parentheses applying to this document): a labelling plant for a container (14) having a rim or a collar, comprising a device (21) for supporting and transporting at least one container suspended in an erect position acting from above on the container, means (15) for mounting a heat-shrinkable annular band (10) onto container acting from below, means (see paragraph 27) being provided to cause label to adhere to container by heat-shrinkage.

The subject-matter of claim 1 differs from this known plant in that means for mounting a heat-shrinkable annular band onto container comprise at least one movable support plate for the label disposed vertically with which means for causing the heat-shrinkable annular band to adhere by heat-shrinkage are associated.

The subject-matter of claim 1 is therefore new (Article 33(2) PCT). The problem to be solved by the present invention may be regarded as facilitating the integration of the labelling line along the container forming and filling line. The solution to this problem proposed in claim 1 of the present application is not disclosed in the prior art (documents D1-D5) and is thus considered as involving an inventive step (Article 33(3) PCT).

2. Claims 2-10 are dependent on claim 1 and as such also meet the requirements of the PCT with respect to novelty and inventive step.

2

in the form of an annular band, so that it rests on the container outer rim. The container provided with the label is then fed through a heating tunnel where the label is made to adhere to the container body by heat. On termination of this operation the container must be again inverted, and then fed to packaging means of usual type.

The aforesaid method is complicated to carry out as each container must be inverted to enable the band-shaped label to be mounted on it from above. This complication is accentuated if the containers contain different products or the same product but of a different flavour. In such a case suitable means must be provided for handling the containers so that the correct label for the product concerned is applied.

An object of this invention is to overcome the drawbacks of the known art within the framework of a simple, reliable and rational solution, able to reduce the final cost.

15

20

٠._.١٢

DISCLOSURE OF THE INVENTION

The invention attains this and other objects by virtue of the characteristics defined in the claims.

In particular, the invention provides a container labelling method comprising the following operative steps:

- a. predisposing a support device for at least one container having a mouth with which an outer rim is associated,
- b. from below, mounting onto the body of said at least one container a heat-shrinkable label in the form of an annular band,
- 25 c. causing the label to adhere to said container.

5

10


15

- 2a

The document DE 10023658 discloses a plant for applying a heat-shrinkable label or band to containers; the labels are transferred to a transport device and then moved to a position beneath the containers hanging from a conveyor belt. Lastly the labels are taken from the transport device and mounted onto the wall of the container, and later on the container with the label mounted thereon is transferred to a heating tunnel for causing each label to adhere to the body of the respective container. All the operations above can be carried out before the container filling.

Notwithstanding the plant disclosed in DE 10023658 presents the drawback that the heating of the labels in a separate location, after the labels have already been inserted onto the container renders difficult to put the labelling device in line with the container forming and filling line.

In other words, the need to provide a heating tunnel separated from the labelling apparatus not always consent a convenient lay out of the labelling line along the container forming and filling line.



2 b

The form of an annular band, so that it rests on the container outer rim.

The container provided with the label is then fed through a heating tunnel where the label is made to adhere to the container body by heat. On termination of this operation the container must be again inverted, and then fed to packaging means of usual type.

The aforesaid method is complicated to sarry out as each container must be inverted to enable the band-shaped label to be mounted on it from above. This complication is accentuated if the containers contain different products or the same product but of a different flavour. In such a case suitable means must be provided for handling the containers so that the correct label for the product concerned is applied.

An object of this invention is to overcome the drawbacks of the known art within the framework of a simple, reliable and rational solution, able to reduce the final cost.

15

20

10

19

ارربها

DISCLOSURE OF THE INVENTION

The invention attains this and other objects by virtue of the characteristics defined in the claims.

In particular, the invention provides a container labelling method comprising the following operative steps:

- a. predisposing a support device for at least one container having a mouth with which an outer rim is associated,
- b. from below, mounting onto the body of said at least one container a heat-shrinkable label in the form of an annular band,
- 25 c. causing the label to adhere to said container.

CLAIMS

5

10

15

- 1. A labelling plant for a container having a rim or collar, comprising a device (3) for supporting and transporting at least one container suspended in an erect position acting from above on the container, means (4) for mounting a heat-shrinkable annular band (5) onto said container acting from below, means (6) being provided to cause said label to adhere to said container by heat-shrinkage, characterised in that said means for mounting a heat-shrinkable annular band onto said container comprise at least one movable support plate (42,52) for the label disposed vertically with which the means (6) for causing the heat-shrinkable annular band (5) to adhere by heat-shrinkage are associated.
- 2. A plant as claimed in claim 1, characterised in that said means (6) for causing the heat-shrinkable annular band (7) to adhere by heat-shrinkage comprises a system for delivering a hot fluid.
- 3. A plant as claimed in claim 2, characterised in that said hot fluid is steam.
- 4. A plant as claimed in claim 2, characterised in that said hot fluid is air.
- 5. A plant as claimed in claim 1, characterised in that said means for causing the heat-shrinkable annular band (5) to adhere to the container comprise a cylinder (54) and a plurality of hot fluid dispensing nozzles (55) supported by the movable support plate (52).
- 6. A plant as claimed in claim 1, characterised by that said movable support plate (42,
 52) is associated with a unit for maintaining vertical the heat-shrinkable annular band (5).

5

- 10-

- 7. A plant as claimed in claim 6, characterised in that said unit for maintaining vertical the heat-shrinkable annular band (7) vertical comprises four vertical rods (45) branching from a second plate (43) connected to the movable support plate (42,52) by virtue of at least one cylinder-piston unit (44).
- 8. A plant as claimed in claim 7, characterised in that said vertical rods (45) are disposed on the perimeter of an imaginary circumference to maintain the label 5 widened while it is mounted onto the container.
- 9. A plant as claimed in claim 1 characterised in that said rods (45) are inserted through corresponding matching holes present in the movable support plate (42,52) and pass beyond said plate to externally receive the heat-shrinkable annular band (5).
- 10. A plant as claimed in claim 6, characterised in that said unit for maintaining vertical the heat-shrinkable annular band (7) vertical comprises four vertical rods (45) branching from a fixed plate (51) and inserted through corresponding matching holes present in the movable support plate (52) supported by the fixed plate (51) by virtue of at least one cylinder-piston unit (53).

20

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

D-BLACK BORDERS
IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
FADED TEXT OR DRAWING
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
☐ SKEWED/SLANTED IMAGES
COLOR OR BLACK AND WHITE PHOTOGRAPHS
☐ GRAY SCALE DOCUMENTS
☐ LINES OR MARKS ON ORIGINAL DOCUMENT
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
☐ OTHER:

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.